

ADVR8032F-NLME-V4

4 SATA H.265 32ch Analog HD DVR F Series

Features :

- Support 32ch 5M-N unreal-time encoding;
- Support AHD, TVI, CVI,CVBS, IP video input;
- HDMI/VGA video output;
- 2U Case, 4SATA(Up to 14TB);
- 1*10/100/1000Mbps auto-sensing Ethernet port, RJ45 port ;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit,unique triple watchdog function
- Support WEB, CMS, VMS, MYEYE Platform;
- Support coaxial control;
- Support Coaxial audio;
- Support intelligent analysis: Human shape detection, face detection, car shape detection

Model :

ADVR8032F-NLME-V4

Interface :



Parameters :



	Model	ADVR8032F-NLME-V4
System	processor	NT98336
Video	Codec	H.265+/H.265/H.264
	preview	32ch 5M-N@12fps(6 in 1)/32ch 4M-N@15fps(6 in 1)/32ch 1080P@15fps(XVI),default 5M-N
	Encode	32ch 5M-N@6fps(6 in 1)/32ch 4M-N@8fps(6 in 1)/32ch 1080P@8fps(XVI),default 5M-N
	Decode	8ch 5M-N@6fps(6 in 1)/16ch 4M-N@8fps(6 in 1)/16ch 1080P@8fps(XVI),default 5M-N
	Multi-mode	Analog:32ch 5M-N/32ch 4M-N/32ch 1080N ;
		Digital to analog conversion : support Hybrid:16ch5M-N(analog)+ 16ch5M(network) IP: 32ch 4K/16ch 5M
Audio	Playback	8ch
	Compression	G.711a
	Coaxial audio	Support
Management	Intercom	Support
	Record mode	Manual>Alarm>Motion detection>Timing
	Inquire mode	Inquire by Time/Calendar/Event/Channel
	Storage mode	HDD Storage, Network Storage
Interface	Backup	Network, USB, SATA
	Video input	32*BNC (Support Coaxitron)
	HDMI output	1*HDMI (MAX:4K)
	VGA output	1*VGA (MAX:1080P)
	Audio I/O	16*in/1*out
	Alarm I/O	16*in/4*out
	Ethernet port	1*10/100/1000Mbps Ethernet port, RJ45 port
	PTZ control	1*RS485, 1*RS232 ; Support for multiple PTZ protocol
General	USB Port	2*USB2.0 ports
	HDD	4*SATA interface (Up to 14TB)
	Temperature	0 °C - + 55 °C
	Humidity	10% -90% RH
	Power supply	12V/6A
	Consumption	<10W (Without HDD)
	Weight	Around 4KG
	Dimension	440mm(L)* 400.5mm(W)* 60mm(H)